



3835() PLASTIC & LEATHER PREP TECHNICAL DATA SHEET

Description

3835() PLASTIC & LEATHER PREP removes mold release agents, fingerprints, grease, wax and other contaminants and leaves plastic and leather substrates clean for coating without softening or distorting. **3835()** leaves no residue.

Features

- Cleans leather and plastic
- Does not soften or distort substrate
- Does not leave residue
- 3 convenient sizes

Typical Properties

Containers	38351 gallon, 38354 quart and 38353 aerosol
Color	Clear
Actual VOC 38353	5.84 #/g1 (700.1 g/l)
Actual VOC 38354 and 38351	6.3 #/g1 (755 g/l)

Check local VOC regulations to ensure compliance in your area.

Handling and Application

APPLICATION: Spray or wipe surface to be painted giving special attention to recessed areas. Follow with a clean dry cloth, wiping in one direction. Change cloths frequently.



STORAGE:



3835() PLASTIC & LEATHER PREP should be stored in a cool dry place with adequate ventilation away from heat, sparks and flames. The shelf life for **38353** is 3 years when stored under normal conditions, while the shelf life for **38354** and **38351** is unlimited.

TECHNICAL CONSULTATION SERVICE

Our Technical Staff is ready to assist you with any questions. You are invited to take advantage of our extensive experience, laboratory services and trained field service representatives. Call (800) 831-1122 for answers to your questions. Hours of operation are Monday through Thursday 8:00 am until 5:00 pm EST and on Friday 8:00 am until 4:30 pm EST.

DISCLAIMER: The information supplied in this document is for guidance only and should not be construed as a warranty. All implied warranties are expressly disclaimed. All users of the materials are responsible for assuring that it is suitable for their needs, environment and use. All data subject to change as SEM deems appropriate.

Users should review the Material Safety Data Sheet (MSDS) and product label for the material to determine possible health hazards, appropriate engineering controls and precautions to be observed in using the material. Copies of the MSDS and product label are available upon request.

SEM Products, Inc.
1685 Overview Dr. Rock Hill SC 29730
Tel: 800/ 831-1122
www.semproducts.com