

**MATERIAL SAFETY
DATA SHEET**



KRYOLAN

IDENTITY (As Used on Label and List)
Mastix, Mastix Matt, TV Mastix

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

Section I Article Nos. 2000-2004, 2012-2014, 2111-2114

Manufacturer's Name Kryolan Corporation	Emergency Telephone Number 1-800- 742-8888 255-3924
---	--

Address (Number, Street, City, State, and ZIP Code) 132 Ninth Street	Telephone Number for Information 415/863-9684
--	---

Date Prepared 3/01/90

San Francisco, CA 94103-2603	Signature of Preparer (optional)
-------------------------------------	---

Section II — Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
---	----------	-----------	--------------------------	--------------

Natural, modified natural and
synthetic resins dissolved in

Ethyl Alcohol	1000 ppm	1000 ppm		
---------------	----------	----------	--	--

Section III — Physical/Chemical Characteristics

Boiling Point	N/A	Specific Gravity (H₂O = 1)	N/A
----------------------	-----	--	-----

Vapor Pressure (mm Hg.)	N/A	Melting Point	90 C
--------------------------------	-----	----------------------	------

Vapor Density (AIR = 1)	0.96	Evaporation Rate (Butyl Acetate = 1)	N/A
--------------------------------	------	---	-----

Solubility in Water
Not water soluble

Appearance and Odor
Viscous amber liquid, ethyl alcohol odor most prominent

Section IV — Fire and Explosion Hazard Data

Flash Point (Method Used) 21° C	Flammable Limits 425° C/igniting temp.	LEL 2.%	UEL 12%
---	--	-------------------	-------------------

Extinguishing Media
Water spray, carbon dioxide foam (in alcohol base) or extinguishing powder

Special Fire Fighting Procedures
None

Unusual Fire and Explosion Hazards
None

Section V — Reactivity Data

Stability	Unstable		Conditions to Avoid
	Stable	X	

Incompatibility (Materials to Avoid) No known incompatibility

Hazardous Decomposition or Byproducts

Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur		

Section VI — Health Hazard Data

Route(s) of Entry: Inhalation? Skin? Ingestion?

Health Hazards (Acute and Chronic) Avoid eye and mucous membrane contact otherwise no known hazard when used on clean, unbroken skin.

Carcinogenicity: NTP? IARC Monographs? OSHA Regulated?
-No Known-

Signs and Symptoms of Exposure

Medical Conditions Generally Aggravated by Exposure

Prolonged exposure: Respiratory problems, broken or irritated skin.

Emergency and First Aid Procedures

EYES: rinse with lots of water/contact doctor immediately. MUCOUS MEMBRANE: rinse carefully w/ Mild Mastix Remover or Surgical Spirit. SWALLOWED: do NOT induce vomiting/see MD

Section VII — Precautions for Safe Handling and Use

Steps to Be Taken in Case Material Is Released or Spilled

Absorb liquid in vermiculite or other absorbant material

ON THE SKIN: Rinse carefully with Mild Mastix Remover or Surgical Spirit

Waste Disposal Method

Waste should not be discharged into domestic drainage systems.

When dried can be disposed of as normal waste.

Precautions to Be Taken in Handling and Storing

Lid must be kept tightly closed when not in use. Store in a cool, dry place.

Other Precautions

Section VIII — Control Measures

Respiratory Protection (Specify Type)

Good ventilation

Ventilation	Local Exhaust	Recommended	Special	N/A
	Mechanical (General)	Yes	Other	N/A

Protective Gloves Not necessary Eye Protection Not necessary

Other Protective Clothing or Equipment Not necessary

Work/Hygienic Practices

Avoid Eye contact, Avoid mucous membrane contact, Avoid excessive inhalation.