----- MATERIAL SAFETY DATA SHEET ------(#8855) LEATHER SHEEN (ACRYLIC FINISHER) Fiebing _____ IDENTITY (As Used on Label and List): (#8855) Leather Sheen (Acrylic Finisher) _____ SECTION I _____ MANUFACTURER'S NAME: FIEBING COMPANY, INC. 516 SOUTH 2ND STREET MILWAUKEE, WI 53204 EMERGENCY TELEPHONE NUMBER: (800) 424-9300 TELEPHONE NUMBER FOR INFORMATION: (414) 271-5011 DATE PREPARED: 03/05/08-----_____ SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION V. O. C. - 0.20 LB/GAL. _____ 9 OSHA ACGIH Hazardous Components (Specific Chemical PEL TLV (optional) Identity: Common Name(s)) _____ *Diethylene Glycol N.E. 6 Monoethyl Ether (CASRN 111-90-0) Other Limits Recommended: N.A. *Subject to the Reporting Requirements of Superfund Amendment and Reauthorization Act of 1986. Title III, Section 313. Emergency Planning and Community Right-to-Know and 40CFR372. _____ ______ SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS _____ BOILING POINT: 212 deg F VAPOR PRESSURE (mm Hg.): of water VAPOR DENSITY (AIR = 1): of water SPECIFIC GRAVITY (H2O = 1) Approx.: 1.016 MELTING POINT: N.D. EVAPORATION RATE (Butyl Acetate = 1): N.D. SOLUBILITY IN WATER: Miscible APPEARANCE AND ODOR: Milky white liquid; characteristic mild odor. SECTION IV - FIRE AND EXPLOSION HAZARD DATA _____ FLASH POINT (Method Used): N.A. FLAMMABLE LIMITS: LEL: N.A. UEL: N.A. EXTINGUISHING MEDIA: Carbon dioxide or dry chemical for small fires Alcohol-type or all-purpose foam for large fires. SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus (pressure-demand, MSHA/NIOSH-approved or equivalent) and full protective gear.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Material can splatter

```
above 100 deg C/212 deg F. Polymer film can burn, giving
 off oxides of carbon and nitrogen.
-----
             SECTION V - REACTIVITY DATA
_____
STABILITY: Stable
 CONDITIONS TO AVOID: Onset of decomposition is 177 deg
   C/350 deg F.
INCOMPATIBILITY (Materials to Avoid):
HAZARDOUS DECOMPOSITION OR BYPRODUCTS:
HAZARDOUS POLYMERIZATION: Will Not Occur
 CONDITIONS TO AVOID: N.A.
_____
           SECTION VI - HEALTH HAZARD DATA
_____
ROUTE(S) OF ENTRY:
 INHALATION? Yes
 SKIN? Yes
 INGESTION? Yes
HEALTH HAZARDS (Acute and Chronic): Inhalation - Vapor or
 spray mist can cause headache, nausea and irritation of
 the nose, throat and lungs. Eye Contact - Irritation upon
 direct contact. Skin Contact - Irritation upon repeated
 or prolonged contact. Ingestion - Slightly toxic. May
 product signs of intoxication.
CARCINOGENICITY:
 NTP? No
 IARC MONOGRAPHS? No
 OSHA REGULATED? No
SIGNS AND SYMPTOMS OF EXPOSURE: As noted above.
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: None
 known.
EMERGENCY AND FIRST AID PROCEDURES: Inhalation - Move
 subject to fresh air. Eye Contact - Flush with clean
 water for 15 minutes. See a physician if irritation
 persists. Skin Contact - Wash with soap and water.
 Ingestion - Give two glasses of water to drink, induce
 vomiting. Call a physician.
_____
   SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE
_____
STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:
 Floor may be slippery; dike and contain spill and absorb
 with inert material.
WASTE DISPOSAL METHOD: Coagulate the emulsion by the
 stepwise addition of ferric chloride and lime. Dispose of
 according to federal, state, county and local
 regulations.
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Keep from
 freezing. Product may coagulate. Keep container closed
 when not in use. Store between 34 deg F and 120 deg F.
OTHER PRECAUTIONS: Avoid skin contact. Avoid eye contact.
 Avoid breathing mist or vapors. Do not ingest.
_____
           SECTION VIII - CONTROL MEASURES
_____
```

RESPIRATORY PROTECTION (Specify Type): Wear suitable respirator (MSHA/NIOSH-approved or equivalent) where exposure limits are exceeded. VENTILATION: LOCAL EXHAUST: Acceptable MECHANICAL (General): Adequate SPECIAL: N.A. OTHER: N.A. PROTECTIVE GLOVES: Impervious EYE PROTECTION: Chemical splash goggles. OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Apron, eye bath, safety shower. WORK/HYGIENIC PRACTICES: Wash thoroughly after handling. _____ N.D. = NOT DETERMINED N.E. = NOT ESTABLISHED N/A = NOT APPLICABLE _____ DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES: Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representation as to the accuracy or completeness of the information contained therein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s). A request has been made to the manufacturer to approve the contents of this material safety data sheet. Upon receipt a new MSDS will be made available. _____ COMPAS Code: 12970500